



CAPFEEDER

HIGH-PERFORMANCE FEEDER FOR BEVERAGE CLOSURES

With the INTRAVIS CapFeeder you get the most powerful feeder on the market for your closure production. With conveying speeds of more than 280,000 closures per hour, the CapFeeder forms an outstanding team in combination with the INTRAVIS CapWatcher®.



FIND OUT
MORE.



The CapFeeder orients and transports up to 80 closures per second

The savings potentials of the total cost of ownership (TCO) are particularly outstanding if you combine the CapFeeder with an INTRAVIS inspection system. At full capacity, an INTRAVIS Closure Line easily **inspects, sorts, and packages the output of two 72-cavity machines with a 2-second cycle time - saving you a complete inspection line!**

Different combinations of line layouts and intermediate buffers offer a wide range of configurations to meet different layout needs. In close cooperation with you, we will work out **the optimal solution for your closure production.**

EASY HANDLING, HIGH EFFICIENCY

In everyday use, the CapFeeder is characterized by easy and efficient handling. If closures are statically charged, the charge is completely neutralized by an in-

tegrated ion bar. This eliminates the risk of misaligned closures so the inspection line can reach its full potential.





CAPFEEDER

HIGH-PERFORMANCE FEEDER FOR BEVERAGE CLOSURES



The INTRAVIS Capfeeder requires no tools for a format change

Changing the closure design, for example from PCO1810 to PCO1881, **can be done without tools** and in just a few steps. Even larger format changes, such as from 26mm to 38mm, can be carried out in no time at all. The subsequent validation of your inspection system can be carried out quickly and easily thanks to the convenient infeed of the appropriate test parts.

The CapFeeder is **an innovative, cost efficient and easy to handle solution**, offering a truly valid production process with the security of high-quality closure production and great savings potential for your inspection line! **Contact us. We are happy to help.**

Speed

Up to 288.000 parts / hour

Closure dimensions

Diameter 25 – 42 mm
Height 7 – 25 mm